



Product Information:
GOLDEN FILM 20W-50
Classic Motor Oil

Description:

Golden Film SAE 20W-50 Classic Motor Oil is specialist high quality, low detergent/dispersant multigrade lubricant. This oil is suitable for use in naturally aspirated four stroke petrol and diesel engines.

Applications:

Golden Film SAE 20W-50 Classic Motor Oil is recommended for use in veteran, classic and vintage cars, motorcycles, commercial vehicles and tractors, where engine design and tolerances prohibit the use of modern high additive level oils.

Golden Film SAE 20W-50 Classic Motor Oil is a low dispersant oil and allows any solid contaminants to drop harmlessly into the sump. This is an important feature where early methods of oil filtration, such as mesh gauzes or strainers are fitted.

The multigrade properties of Golden Film SAE 20W-50 provide improved cold start circulation whilst maintaining good working oil pressure.

Performance Levels:

API CC/SF
MIL-L-2104B

Physical Characteristics:

Appearance	Amber liquid
Density @ 15°C	0.876
Kinematic Viscosity @ 40°C (cSt)	131.8
Kinematic Viscosity @ 100°C (cSt)	16.9
Viscosity Index	140
Cold Crank Simulator @ -15°C (mPas)	9500 max
Pour Point (°C)	-35
Closed Flash Point (°C)	210
Base Number (mgKOH/g)	7.5

Figures based on average production values

Part No.s: GFM001, GFM005

(TDS GoldenFilm 20W50– 160116 Issue 4)

